


658 Series Ball Valve



Configure your exact valve



SCAN ME

Design Considerations

The 658 Series 90 Degree Rotary Valve design promotes multiple configurations to fit the exact end use application. The 658 Series Valve was originally designed for the water purification industry and is NSF Standard 42 Certified. Filled Polypropylene is available for chemical resistance applications.

Specifications:

Maximum Operating Pressure — 160 psi	Maximum Operating Temperature — 180°F	Ball Through Hole Diameter — .170
Material Options	Gray PVC (Standard), White PVC, White Polypropylene	
Seal Options	Buna-N, Ethylene Propylene, Fluoroelastomer (Viton®)	
End Options	1/4 Female NPT x 1/4 SMC Push-To-Connect 1/4 Female NPT x 3/8 SMC Push-To-Connect	

Example of how to order:

Body Material	Inlet End	Outlet End	Seal
White Filled Poly	1/4 FNPT	1/4 SMC	Buna-N

Part Number: WFP 658-4F4SMC-B

The handle will lie over the Side port when the valve is in the open position. SMC Part Numbers are a description of the valve as read left to right, Bottom Inlet to Side Outlet.

Example: WFP 658-4F4SMC-B = 1/4 FNPT Bottom Inlet x 1/4 SMC Side Outlet