

Female Quick Disconnect

10-32 FEMALE



Design Consideration



- Female Quick Disconnect
- Receiver for Male Quick Disconnects
- Supplied with Electroless Nickel Plated Nut and lockwasher

Example of how to order

Type: Female Quick Disconnect **End Option:** 10-32 Female

Part Numbers are a description of the valve as read left to right, Inlet Port to Outlet Port.

QD FEMALE,10-32F = Female Quick Disconnect, 10-32F

Item #	Image	Body	End Option	Panel Mount Hole	Maximum Panel Thickness	Maximum Operating Pressure	Maximum Operating Temperature
QD FEMALE,W/NEEDLE,10-32F		QD FEMALE	10-32 Female	0.500 in	0.500 in	125 psi	180 °F
QD FEMALE,W/NEEDLE,10-32M		QD FEMALE	10-32 Male	0.500 in	0.500 in	125 psi	180 °F

Item #	Image	Body	End Option	Panel Mount Hole	Maximum Panel Thickness	Maximum Operating Pressure	Maximum Operating Temperature
QD FEMALE,W/NEEDLE,1/16B	 QD FEMALE 1/16B larger image	QD FEMALE	1/16 Barb	0.500 in	0.500 in	125 psi	180 °F
QD FEMALE,W/NEEDLE,3/32B	 QD FEMALE 3/32B larger image	QD FEMALE	3/32 Barb	0.500 in	0.500 in	125 psi	180 °F
QD FEMALE,W/NEEDLE,1/8B	 QD FEMALE 1/8B larger image	QD FEMALE	1/8 Barb	0.500 in	0.500 in	125 psi	180 °F