

Swivel Needle Valve (Male x Female)

1/8" NPT



Configure your exact valve



SCAN ME

Design Considerations

- 1/8 NPT Swivel Body for easy orientation after installation
- 6.5 Turn Adjustment Needle
- Smooth or Ribbed ABS Knob in Black or Gray

*** Knobs are Optional ***

Specifications:

Type	Needle Valve
Needle Option	6.5 Turn Brass
Seal Option	Buna-N, Ethylene Propylene, Fluoroelastomer (Viton®)
Material	BODY - Electroless Nickel Plated Brass
Input Port	1/8 Male NPT
Output Port	1/8 Female NPT
Knob	No Knob Smooth Black ABS, Smooth Gray ABS Ribbed Black ABS, Ribbed Gray ABS
Maximum Operating Pressure	0 to 125 psi
Maximum Operating Temperature	180 °F
Flow Rate	2.5 SCFM at 50 psi

Example of how to order:

Type	Seal	Needle	Inlet Port	Outlet Port	Knob
Swivel Needle Valve	Buna	6.5 Turn Needle	1/8 MNPT	1/8 FNPT	No Knob

Part Numbers are a description of the valve as read left to right, Inlet Port to Outlet Port.

Example: SWNV2NC-B,6.5T,1/8M,1/8F,NO KNOB= Swivel Needle Valve, Buna Seals, 6.5 Turn Needle, 1/8 Male Inlet x 1/8 Female Outlet, No Knob